


CONNECTOR FEATURES

PRODUCT TYPE	DIN43650/A CONNECTOR FIELD ATTACHABLE
HOUSING COLOUR	BLACK
HEIGHT HOUSING	30mm
TYPE CONTACTS	SCREW WITH CONDUCTOR PROTECTION
CONTACT SPACING	18mm
NUMBER OF POLES	2POLES-EARTH
EARTH POSITIONING	H.12
CABLE EXIT	PG9/PG11 UNIFIED
SUITABLE CABLE	FROM $\phi 6mm$ TO $\phi 11mm$
MAXIMUM CONDUCTOR SIZE	1.5mm
FIXING SCREW	M3X0.5 L=32.5mm
PROFILED GASKET	NBR
PROTECTION CLASS	IP65
CIRCUIT TYPE	WITH SPECIAL ENERGY SAVING CIRCUIT
VOLTAGE	24V
CONNECTOR WITH H.T.P. LOGO	




TOLLERANZE	± 0.2	DISIGNAZIONE	06-02-15	SCALA	1:1	DISIGNO N.	1-4
UDM	ANGOLID	LORENZO CIMINO	CONTROLATO				

DESCRIZIONE
CONNECTOR DIN43650/A.G1 SERIES CONTACT SPACING 18mm, 2P+E,
BLACK HOUSING WITH SPECIAL ENERGY SAVING CIRCUIT 24V,
PG9/11 UNIF. CONNECTOR WITH H.T.P. LOGO

TPO
G1

CODE CLIENTE



H.T.P. HIGH TECH PRODUCTS

CODE
G1NUZES1